Pages: 3

Reg No.:__

Name:

APJ ABDUL KALAM TECHNOLOGICAL UNIVERSITY

Sixth semester B.Tech examinations (S), September 2020

Course Code: ME302 Course Name: Heat and Mass Transfer

Use of heat and mass transfer data book permitted

Max. Marks: 100

Duration: 3 Hours

Marks

PART A Answer any three full questions, each carries 10 marks.

1 a) Derive the expression for critical thickness of a cylinder. What is the importance (4) of critical thickness of insulation?

- b) A hollow sphere of inner radius 30 mm and outside radius 50 mm is electrically (6) heated at its inner surface at a constant rate of 10^5 W/m^2 . The outer surface is exposed to a fluid at 30 °C with h = 170 W/m²K. Thermal conductivity of the material is 20 W/m K. Calculate the inner and outer surface temperatures.
- a) Air at velocity of 3m/s and at 20°C flows over a flat plate along the length. The (5) length, width and thickness of the plate are 100cm, 50cm, 2cm respectively. The top surface of the plate is maintained at 100°C. Calculate the heat lost by the plate and temperature at bottom surface of the plate for steady state conditions. Thermal conductivity of plate material is 23 W/mK
 - b) A vertical plate 15cm high and 10cm wide is maintained at 140°C. Calculate the (5) maximum heat dissipation rate from both sides of the plate in ambient air at 20°C by free convection
- 3 a) Derive the general heat conduction equation in Cartesian coordinates, state the (8) assumptions.
 - b) Good electrical conductors usually have the property of high thermal (2) conductivity. Why?
- 4 a) Using Buckingham pi theorem derive the expression for flow through a tube (7) under forced convection. Make suitable assumptions
 - b) Explain the importance of hydrodynamic and thermal boundary layers in heat (3) transfer.

03000ME302052001

PART B

Answer any three full questions, each carries 10 marks.

- 5 a) An aluminium sphere weighing 6kg and initially at temperature of 350° C is (7) suddenly immersed in a fluid at 30° C with h = 60 W/m² C. Estimate the time required to cool the sphere to 100° C.
 - b) Define fin efficiency and effectiveness (3)
- 6 a) Explain the features of pool boiling process with the curve (5)
 - b) Derive an expression for heat flow from a fin with tip insulated (derivation may (5) start from solution of general fin differential equation, $\Theta = C_1 e^{mx} + C_2 e^{-mx}$, with clear statement of boundary conditions)
- 7 a) Classify heat exchangers based on flow direction .Explain why a counter flow is (3) superior arrangement. When do we use specifically use parallel flow heat exchangers?
 - b) Derive the expression for LMTD of a parallel flow heat exchanger (7)
- 8 The following are the details of a parallel flow heat exchanger Heat capacity of (10) cold flow entering at 40°C = 20000 W/K, Heat capacity of hot flow entering at 150° C = 10000 W/K, A=30 m², U=500 W/m²K. Determine heat transfer rate and exit temperatures

PART C

Answer any four full questions, each carries 10 marks.

- 9 a) State and prove Kirchhoff's law of radiation
 - b) Two black discs of diameter 50 cm each are placed parallel to each other (7) concentrically at a distance of 1m. Disc temperatures are 727°C and 227°C.
 Calculate the heat transfer between discs if no other surface is present in between.

(3)

- 10 a) What are radiation shields? Mention some of their applications (2)
 - b) Two concentric cylinders have inner and outer radius with 5cm and 10cm and (8) length 20cm. Calculate the view factors
- Determine the heat lost by radiation per meter length of 80mm diameter pipe at (10)
 300°C, if (i)Located in a large room with red brick walls at temperature of 27°C
 (ii)Enclosed in a 160 mm diameter red brick conduit at a temperature of 27°C.
 Emisssivities of pipe material and brick 0.79 and 0.93 respectively
- 12 a) State ficks law of mass diffusion, explaining all the terms (3)
 - b) Air at atm temperature 25°C, 18% RH flows through a pipe of 25mm inside dia (7)

03000ME302052001

with a velocity of 4.5m/s. The inside is constantly wetted with water so as to maintain a water film on the inside the surface. Determine evaporation rate per m² of surface area. Kinematic viscocity =15.6 x 10⁻⁶ m²/s, Sc = 0.6, Diffusion coefficient = $0.26 \times 10^{-4} \text{ m}^2$ /s, density under saturated conditions at 25°C = 0.231 kg/m³.

- 13 Derive the expression for mass transfer for the case of isothermal evaporation (10) from the bottom of a small tube through surrounding stagnant gas.
- 14 a) Discuss the analogy between heat transfer and mass transfer (5)
 - b) Estimate the diffusion rate of water from bottom of a test tube 1.5cm in diameter (5) and 15cm long into dry atmospheric air at 25° C. D = 25.6 x 10^{-6} m²/s
